



OPERATING TEMPERATURE	
DOOR	TRACKSIDE WALLSIDE

REQUIRED FOR PRODUCTION

4" FREEZER - MODEL 603LWT

FOR:	P.O.#:	DATE:	DRAWN BY:	APPROVED BY:	
JOB:	F.O.#:	TAG:	CHECKED BY:	LAST REVISION:	
DOOR # QTY	W. I. C. WIDTH IN CLEAR	H. I. C. HEIGHT IN CLEAR	DOOR TYPE	JAMB DEPTH	SERIAL NUMBER

COLD STORAGE DOOR
BI-PART
MANUAL

- ### INSTALLATION REQUIREMENTS
- I. Floor under door must be level and smooth
 - II. Wall behind header and casings must be smooth in a common plane.
 - III. Mounting holes 3/4" diameter (drilled in field - by others). Stayrollers installed in field - by others.

DOOR PANEL AND FRAME MANUAL DOORS

- A. DOOR PANEL
- 24 GA white stucco steel
 - 24 GA white smooth steel
 - 24 GA 304 2B smooth stainless steel
 - OTHER:

B. Extruded aluminum door frame.

- C. CASINGS AND HEADER
- Wood clad with:
 - Gray plastic clad with:

- 24 GA white stucco steel
- 24 GA white smooth steel
- 24 GA 304 2B smooth stainless steel
- OTHER:

D. FREEZER DOOR (4" and 6" doors only)
Heaters are standard equipment on all freezer doors - 110V connection required.
(110V connections supplied in field - by others).

OPTIONS

- E. FASTENERS
- Through bolts (frame drilled in field - by others)
 - OTHER:

F. ADDITIONAL HEATED SEALS

- G. INSIDE JAMBS
- Wood clad with:
 - Gray plastic clad with:

- 24 GA white stucco steel
- 24 GA white smooth steel
- 24 GA 304 2B stainless steel
- OTHER:

H. BACKFRAME

- Wood clad with:
- Gray plastic clad with:

- 24 GA white stucco steel
- 24 GA white smooth steel
- 24 GA 304 2B smooth stainless steel
- OTHER:

- I. KICKPLATES Trackside Wallside
- Height: 18" 24" 36" 48" OTHER:
- Aluminum diamond tread (1/8" thick)
 - 18 GA 304 2B stainless steel
 - OTHER:

J. LOCKING DEVICE - Hasp Type

- TRACKSIDE WALLSIDE
- with emergency release
- no emergency release

K. () VISION PANEL - 12" x 14" Insulated Heated

