



OPERATING TEMPERATURE	
DOOR	TRACKSIDE WALLSIDE

REQUIRED FOR PRODUCTION	

BI-PART FREEZER MODEL 603LWTE

FOR: _____ P.O.#: _____ DATE: _____
 JOB: _____ F.O.#: _____ TAG: _____
 W. I. C. WIDTH IN CLEAR H. I. C. HEIGHT IN CLEAR DOOR TYPE LOCK OPERATOR VOLTAGE JAMB DEPTH SERIAL NUMBER

DRAWN BY: _____ APPROVED BY: _____
 CHECKED BY: _____ LAST REVISION: _____

**BI-PART HORIZONTAL SLIDE
COLD STORAGE DOOR**
POWER FREEZER
Model 603LWTE

INSTALLATION REQUIREMENTS

- I. Floor under door must be level and smooth
 - II. Wall behind header and casings must be smooth in a common plane.
 - III. Mounting holes 3/4" diameter (drilled in field - by others). Stayrollers installed in field - by others.
- DOOR PANEL AND FRAME POWER OPERATED DOORS**
- A. OPERATOR, SINGLE PHASE INPUT VOLTAGE REQUIRED. (3 phase supply requires 1 capped leg). Operator and control box prewired at factory. Exposed wiring is sealight conduit.
 - B. Safety reverse. Door will reverse to full open position and stop if object is struck while closing.
 - C. (2.) 24V. pullcord switches. Pullcord switches wired to operator at jobsite - by others.
- DOOR PANEL AND FRAME**

- D. DOOR PANEL
- 26 GA white stucco steel
 - 26 GA white smooth steel
 - 24 GA 304 2B stainless steel
 - OTHER:
- E. Extruded aluminum door frame.
- F. CASINGS AND HEADER
- Wood clad with Gray plastic clad with
 - 26 GA white stucco steel
 - 26 GA white smooth steel
 - 24 GA 304 2B stainless steel
 - OTHER:

- G. FREEZER DOOR (4" and 6" doors only)
- Heaters are standard equipment on all freezer doors - 110V connection required. Freezers are supplied with 1 standard and 1 heated pullcord. Heated pullcords contain 10 watt heater cartridge - 110V connection required. (110V connections supplied in field - by others).
- OPTIONS**
- H. ADDITIONAL HEATED SEALS
- I. FASTENERS
- Through bolts (frame drilled in field - by others)
 - OTHER :
- J. INSIDE JAMBS
- Wood clad with Gray plastic clad with
 - 26 GA white stucco steel
 - 26 GA white smooth steel
 - 24 GA 304 2B stainless steel
 - OTHER:

- K. BACKFRAME
- Wood clad with Gray plastic clad with
 - 26 GA white stucco steel
 - 26 GA white smooth steel
 - 24 GA 304 2B stainless steel
 - OTHER:
- L. KICKPLATES Trackside Wallside
- Height: 18" 24" 36" 48" OTHER:
- Aluminum diamond tread (1/8" thick)
 - 18 GA 304 2B stainless steel
 - OTHER:

- M. LOCKING DEVICE - Hasp Type
- TRACKSIDE WALLSIDE
 - With power cut-off and emergency release with power cut-off (NO EMERGENCY RELEASE)
- N. VISION PANEL - 12" x 14" Insulated Heated
- O. MOTION DETECTOR Open Safety
- P. PHOTOCELL Open Safety
- Q. POM (Partial Open Mode)
- R. PUSHBUTTONS Single Double Triple
- S. In addition to pullcords In lieu of pullcords
- T. RADIO CONTROLS (1 receiver - 2 transmitters)
- U. TIME DELAY CLOSE
- V. LOOP DETECTOR Open Safety

