



**INSTALLATION REQUIREMENTS**

- I. Floor under door must be level and smooth
- II. Wall behind face frame must be smooth in a common plane.
- III. Mounting holes 3/4" diameter (drilled in field - by others).

**DOOR PANEL AND FRAME**

- A. DOOR PANEL
  - 24 GA white stucco embossed
  - 24 GA 304 2B stainless steel
  - 090 white (stucco embossed style) FRP
  - OTHER:
- B. FACE FRAME
  - Wood clad 24ga white stucco embossed
  - Ext. plastic foamed in place 24ga white stucco
  - Wood clad 24ga 304-2B stainless steel
  - OTHER:
- C. LATCH
  - Padlockable  Keyed Cylinder
  - Polished chrome
  - Stainless steel
  - OTHER
- D. INTERIOR RELEASE
  - MUSHROOM BUTTON & Nylon Push Rod (Frost Free)
  - BUMP BAR over mushroom button
  - PANIC BAR (NO EXTERIOR RE-ENTRY)
  - PANIC BAR with Von Duprin 373 lever latch
  - KASON 483 RELEASE
  - OTHER:
- E. HINGE
  - Cam lift polished chrome
  - Cam lift stainless steel
  - 1277 zinc plate finish
  - OTHER:
- F. FASTENERS
  - THROUGH BOLTS (installed in field - by others)
  - GALV LAG BOLTS (installed in field - by others)
  - OTHER:

**OPTIONS**

- G.  FREEZER DOOR (4" and 6" doors only)
  - 110V (108 watts, 1 AMP) electric defrost system at four sides of gasket contact area. Separate 110V connection required in field - by others.
- H.  INSIDE JAMBS
  - Wood clad 24ga white stucco embossed
  - Ext. plastic foamed in place 24ga white stucco
  - Wood clad 24ga 304-2B stainless steel
  - OTHER:
- I.  MIRROR IMAGE BACKFRAME
  - Wood clad 24ga white stucco embossed
  - Ext. plastic foamed in place 24ga white stucco
  - Wood clad 24ga 304-2B stainless steel
  - OTHER:
- J.  DOOR CLOSER
  - LCN-1460 interior mounted
  - 1097 exterior mounted
  - OTHER:
- K.  HOOD
  - MATCHED TO HINGESIDE PANEL STEEL
  - OTHER:
- L.  KICKPLATES  Hingeside  Wallside
  - Height:  18"  24"  36"  48"  OTHER:
  - Aluminum diamond tread (1/8" thick)
  - 18 GA 304 2B stainless steel
  - OTHER:
- M.  LEADING EDGE CASTER
- N.  PILFER PROOF HARDWARE
- O.  VISION PANEL
  - 12" x 14" Insulated
  - 12" x 14" Heated
  - OTHER:

OPERATING TEMPERATURE		
DOOR	HINGESIDE	WALLSIDE
REQUIRED FOR PRODUCTION		

APPROVED BY: \_\_\_\_\_ DATE: \_\_\_\_\_

**IMPORTANT:**  
Factory may alter door construction and hardware from design illustrated. Factory will not exceed illustrated clearances.

Design drawings are for use to verify size, required clearances, and providing confirmation of options requested. Actual production design and components may vary but will not exceed illustrated clearances.

**LEFT HINGE TO OPEN - AS SHOWN**  
**RIGHT HINGE - MIRROR IMAGE**

<b>FOR:</b>		<b>P.O.:</b>		<b>TAG:</b>	
<b>JOB:</b>		<b>F.O.#:</b>		<b>Serial Number</b>	
<b>DOOR #</b>	<b>QTY</b>	<b>WIDTH IN CLEAR</b>	<b>HEIGHT IN CLEAR</b>	<b>DOOR TYPE</b>	<b>JAMB DEPTH</b>

<b>DRAWN BY:</b>	<b>APPROVED BY:</b>
<b>CHECKED BY:</b>	<b>LAST REVISION:</b>
<b>INFITTING HINGE</b>	
<b>COLD STORAGE DOOR</b>	
SINGLE LEAF      4" COOLER	
<b>MODEL 540TN</b>	

