



**INSTALLATION REQUIREMENTS**

- I. Floor under door must be level and smooth
- II. Wall behind face frame must be smooth in a common plane.
- III. Mounting holes 3/4" diameter (drilled in field - by others).

**DOOR PANEL AND FRAME**

- A. DOOR PANEL
  - 24 GA white stucco embossed
  - 24 GA 304 2B stainless steel
  - 090 white (stucco embossed style) FRP
  - OTHER:
- B. FACE FRAME
  - Wood clad 24ga white stucco embossed
  - Ext. plastic foamed in place 24ga white stucco
  - Wood clad 24ga 304-2B stainless steel
  - OTHER:
- C. LATCH
  - Padlockable  Keyed Cylinder
  - Polished chrome
  - Stainless steel
  - OTHER
- D. INTERIOR RELEASE
  - MUSHROOM BUTTON & Nylon Push Rod (Frost Free)
  - BUMP BAR over mushroom button
  - PANIC BAR (NO EXTERIOR RE-ENTRY)
  - PANIC BAR with Von Duprin 373 lever latch
  - KASON 483 RELEASE
  - OTHER:
- E. HINGE
  - Cam lift polished chrome
  - Cam lift stainless steel
  - 1277 zinc plate finish
  - OTHER:
- F. FASTENERS
  - THROUGH BOLTS (installed in field - by others)
  - GALV LAG BOLTS (installed in field - by others)
  - OTHER:

**OPTIONS**

- G.  FREEZER DOOR (4" and 6" doors only)
  - 110V (108 watts, 1 AMP) electric defrost system at four sides of gasket contact area. Separate 110V connection required in field - by others.
- H.  INSIDE JAMBS
  - Wood clad 24ga white stucco embossed
  - Ext. plastic foamed in place 24ga white stucco
  - Wood clad 24ga 304-2B stainless steel
  - OTHER:
- I.  MIRROR IMAGE BACKFRAME
  - Wood clad 24ga white stucco embossed
  - Ext. plastic foamed in place 24ga white stucco
  - Wood clad 24ga 304-2B stainless steel
  - OTHER:
- J.  DOOR CLOSER
  - LCN-1460 interior mounted
  - 1097 exterior mounted
  - OTHER:
- K.  HOOD
  - MATCHED TO HINGESIDE PANEL STEEL
  - OTHER:
- L.  KICKPLATES  Hingeside  Wallside
  - Height:  18"  24"  36"  48"  OTHER:
  - Aluminum diamond tread (1/8" thick)
  - 18 GA 304 2B stainless steel
  - OTHER:
- M.  LEADING EDGE CASTER
- N.  PILFER PROOF HARDWARE
- O.  VISION PANEL
  - 12" x 14" Insulated
  - 12" x 14" Heated
  - OTHER:

OPERATING TEMPERATURE		
DOOR	HINGESIDE	WALLSIDE
REQUIRED FOR PRODUCTION		

APPROVED BY: \_\_\_\_\_ DATE: \_\_\_\_\_

**IMPORTANT:**  
Factory may alter door construction and hardware from design illustrated. Factory will not exceed illustrated clearances.

**RIGHT HINGE TO OPEN - AS SHOWN**  
**LEFT HINGE - MIRROR IMAGE**

<b>FOR:</b>		<b>P.O.:</b>		<b>TAG:</b>	
<b>JOB:</b>		<b>F.O.#:</b>		<b>Serial Number</b>	
<b>DOOR #</b>	<b>QTY</b>	<b>WIDTH IN CLEAR</b>	<b>HEIGHT IN CLEAR</b>	<b>DOOR TYPE</b>	<b>JAMB DEPTH</b>

<b>DRAWN BY:</b>	<b>APPROVED BY:</b>
<b>CHECKED BY:</b>	<b>LAST REVISION:</b>
<b>INFITTING HINGE</b>	
<b>COLD STORAGE DOOR</b>	
SINGLE LEAF      4" FREEZER	
<b>MODEL 840LWT</b>	

