



INSTALLATION REQUIREMENTS

- I. Floor under door must be level and smooth
- II. Wall behind face frame must be smooth in a common plane.
- III. Mounting holes 3/4" diameter (drilled in field - by others).

DOOR PANEL AND FRAME

- A. DOOR PANEL
 - 24 GA white stucco embossed
 - 24 GA 304 2B stainless steel
 - 090 white (stucco embossed style) FRP
 - OTHER:
- B. FACE FRAME
 - Wood clad 24ga white stucco embossed
 - Ext. plastic foamed in place 24ga white stucco
 - Wood clad 24ga 304-2B stainless steel
 - OTHER:
- C. LATCH
 - Padlockable Keyed Cylinder
 - Polished chrome
 - Stainless steel
 - OTHER
- D. INTERIOR RELEASE
 - MUSHROOM BUTTON & Nylon Push Rod (Frost Free)
 - BUMP BAR over mushroom button
 - PANIC BAR (NO EXTERIOR RE-ENTRY)
 - PANIC BAR with Von Duprin 373 lever latch
 - KASON 483 RELEASE
 - OTHER:
- E. HINGE
 - Cam lift polished chrome
 - Cam lift stainless steel
 - 1277 zinc plate finish
 - OTHER:
- F. FASTENERS
 - THROUGH BOLTS (installed in field - by others)
 - GALV LAG BOLTS (installed in field - by others)
 - OTHER:

OPTIONS

- G. FREEZER DOOR (4" and 6" doors only)
 - 110V (108 watts, 1 AMP) electric defrost system at four sides of gasket contact area. Separate 110V connection required in field - by others.
- H. INSIDE JAMBS
 - Wood clad 24ga white stucco embossed
 - Ext. plastic foamed in place 24ga white stucco
 - Wood clad 24ga 304-2B stainless steel
 - OTHER:
- I. MIRROR IMAGE BACKFRAME
 - Wood clad 24ga white stucco embossed
 - Ext. plastic foamed in place 24ga white stucco
 - Wood clad 24ga 304-2B stainless steel
 - OTHER:
- J. DOOR CLOSER
 - LCN-1460 interior mounted
 - 1097 exterior mounted
 - OTHER:
- K. HOOD
 - MATCHED TO HINGESIDE PANEL STEEL
 - OTHER:
- L. KICKPLATES Hingeside Wallside
 - Height: 18" 24" 36" 48" OTHER:
 - Aluminum diamond tread (1/8" thick)
 - 18 GA 304 2B stainless steel
 - OTHER:

OPERATING TEMPERATURE		
DOOR	HINGESIDE	WALLSIDE
REQUIRED FOR PRODUCTION		

APPROVED BY: _____ DATE: _____

IMPORTANT:
Factory may alter door construction and hardware from design illustrated. Factory will not exceed illustrated clearances.

RIGHT HINGE TO OPEN - AS SHOWN
LEFT HINGE - MIRROR IMAGE

FOR:		P.O.:		DATE:			
JOB:		F.O.#:		TAG:			
DOOR #	QTY	WIDTH IN CLEAR	HEIGHT IN CLEAR	DOOR TYPE	JAMB DEPTH	HINGE LOCATION	SERIAL NUMBER

DRAWN BY: _____ APPROVED BY: _____
 CHECKED BY: _____ LAST REVISION: _____

INFITTING HINGE
COLD STORAGE DOOR
 SINGLE LEAF 4" FREEZER
MODEL 840LWT

- M. LEADING EDGE CASTER
- N. PILFER PROOF HARDWARE
- O. VISION PANEL
 - 12" x 14" Insulated
 - 12" x 14" Heated
 - OTHER:

