



OPERATING TEMPERATURE	
DOOR	TRACKSIDE WALLSIDE

REQUIRED FOR PRODUCTION

FREEZER - MODEL V603LWTE

FOR:		P.O.#:		DATE:		DRAWN BY:		APPROVED BY:	
JOB:		F.O.#:		TAG:		CHECKED BY:		LAST REVISION:	
DOOR #	QTY	W.I.C.	H.I.C.	DOOR TYPE	JAMB DEPTH	OPERATOR VOLTAGE	SERIAL NUMBER		
		WIDTH IN CLEAR	HEIGHT IN CLEAR	Freezer	NO				

**VERTICAL SLIDE  
COLD STORAGE DOOR**  
POWER  
Model V603LWTE

**INSTALLATION REQUIREMENTS**

- I. Floor under door must be level and smooth
- II. Wall behind header and casings must be smooth in a common plane.
- III. Mounting holes 3/4" diameter (drilled in field - by others).

**DOOR PANEL AND FRAME MANUAL DOORS**

- A. DOOR PANEL**
- 24 GA white stucco steel
  - 24GA white smooth steel
  - 24 GA 304 stucco stainless steel
  - OTHER:

- B. Extruded aluminum door frame.**

- C. CASINGS AND HEADER**
- Wood clad with:
  - Gray plastic clad with:
  - 24 GA white stucco steel
  - 24 GA white smooth steel
  - 24 GA 304 stucco stainless steel
  - OTHER:

- D.  FREEZER DOOR (4" and 6" doors only)**
- Heaters are standard equipment on all freezer doors - 110V connection required.  
(110V connections supplied in field - by others).

**OPTIONS**

- E. FASTENERS**
- Nylon bolts (frame drilled in field - by others)
  - OTHER:

- F.  ADDITIONAL HEATED SEALS**

- G.  INSIDE JAMBS**
- Wood clad with:
  - Gray plastic clad with:
  - 24 GA white stucco steel
  - 24 GA white smooth steel
  - 24 GA 304 2B stainless steel
  - OTHER:

- H.  BACKFRAME**
- Wood clad with:
  - Gray plastic clad with:
  - 24 GA white stucco steel
  - 24 GA white smooth steel
  - 24 GA 304 stucco stainless steel
  - OTHER:

- I.  KICKPLATES  Trackside  Wallside**
- Height:  18"  24"  36"  48"  OTHER:
- Aluminum diamond tread (1/8" thick)
  - 18 GA 304 2B stainless steel
  - OTHER:

- J.  LOCKING DEVICE - Hasp Type**
- TRACKSIDE  WALLSIDE
  - with emergency release
  - no emergency release

- K.  ( ) VISION PANEL - 24" x 24"  Insulated  Heated**

