



OPERATING TEMPERATURE	
DOOR TRACKSIDE	WALLSIDE

BI-PART MANUAL COOLER – MODEL 603TN

FOR:	P.O.#:	DATE:					
JOB:	F.O.#:	TAG:					
DOOR #	QTY	W. I. C. WIDTH IN CLEAR	H. I. C. HEIGHT IN CLEAR	DOOR TYPE	LOCK	JAMB DEPTH	SERIAL NUMBER

DRAWN BY:	APPROVED BY:
CHECKED BY:	LAST REVISION:

COLD STORAGE DOOR
BI-PART
MANUAL

INSTALLATION REQUIREMENTS

- I. Floor under door must be level and smooth
- II. Wall behind header and casings must be smooth in a common plane.
- III. Mounting holes 3/4" diameter (drilled in field - by others).
- IV. Stayrollers installed in field - by others.

DOOR PANEL AND FRAME MANUAL DOORS

- A. DOOR PANEL
 - 26 GA white stucco steel
 - 26 GA white smooth steel
 - 24 GA 304 2B stainless steel
 - OTHER:
- B. Extruded aluminum door frame.
- C. CASINGS AND HEADER
 - Wood clad with:
 - Gray plastic clad with:
 - 26 GA white stucco steel
 - 26 GA white smooth steel
 - 24 GA 304 2B stainless steel
 - OTHER:
- D. FREEZER DOOR (4" and 6" doors only)
Heaters are standard equipment on all freezer doors - 110V connection required.
(110V connections supplied in field - by others).

OPTIONS

- E. FASTENERS
 - Through bolts (frame drilled in field - by others)
 - OTHER:
- F. ADDITIONAL HEATED SEALS
- G. INSIDE JAMBS
 - Wood clad with:
 - Gray plastic clad with:
 - 26 GA white stucco steel
 - 26 GA white smooth steel
 - 24 GA 304 2B stainless steel
 - OTHER:
- H. BACKFRAME
 - Wood clad with:
 - Gray plastic clad with:
 - 26 GA white stucco steel
 - 26 GA white smooth steel
 - 24 GA 304 2B stainless steel
 - OTHER:
- I. KICKPLATES
 - Trackside
 - Wallside
 - Height: 18" 24" 36" 48" OTHER:
 - Aluminum diamond tread (1/8" thick)
 - 18 GA 304 2B stainless steel
 - OTHER:
- J. LOCKING DEVICE: Hasp Type
 - TRACKSIDE
 - WALLSIDE
 - with emergency release
 - no emergency release
- K. () VISION PANEL - 12" x 14" Insulated Heated

