



| OPERATING TEMPERATURE |                    |
|-----------------------|--------------------|
| DOOR                  | TRACKSIDE WALLSIDE |
|                       |                    |
|                       |                    |
|                       |                    |
|                       |                    |

REQUIRED FOR PRODUCTION

COOLER - MODEL V603TNE

|        |     |                |                 |           |            |                  |               |                |  |
|--------|-----|----------------|-----------------|-----------|------------|------------------|---------------|----------------|--|
| FOR:   |     | P.O.#:         |                 | DATE:     |            | DRAWN BY:        |               | APPROVED BY:   |  |
| JOB:   |     | F.O.#:         |                 | TAG:      |            | CHECKED BY:      |               | LAST REVISION: |  |
| DOOR # | QTY | W.I.C.         | W.I.C.          | DOOR TYPE | JAMB DEPTH | OPERATOR VOLTAGE | SERIAL NUMBER |                |  |
|        |     | WIDTH IN CLEAR | HEIGHT IN CLEAR | Cooler    | NO         |                  |               |                |  |

**VERTICAL SLIDE  
COLD STORAGE DOOR**  
POWER  
Model V603TNE

**INSTALLATION REQUIREMENTS**

- I. Floor under door must be level and smooth
- II. Wall behind header and casings must be smooth in a common plane.
- III. Mounting holes 3/4" diameter (drilled in field - by others).

**DOOR PANEL AND FRAME MANUAL DOORS**

- A. DOOR PANEL**
- 24 GA white stucco steel
  - 24GA white smooth steel
  - 24 GA 304 stucco stainless steel
  - OTHER:

- B. Extruded aluminum door frame.**

- C. CASINGS AND HEADER**
- Wood clad with:
  - Gray plastic clad with:

- 24 GA white stucco steel
- 24 GA white smooth steel
- 24 GA 304 stucco stainless steel
- OTHER:

- D.  FREEZER DOOR (4" and 6" doors only)**
- Heaters are standard equipment on all freezer doors - 110V connection required.  
(110V connections supplied in field - by others).

**OPTIONS**

- E. FASTENERS**
- Nylon bolts (frame drilled in field - by others)
  - OTHER:

- F.  ADDITIONAL HEATED SEALS**

- G.  INSIDE JAMBS**
- Wood clad with:
  - Gray plastic clad with:

- 24 GA white stucco steel
- 24 GA white smooth steel
- 24 GA 304 2B stainless steel
- OTHER:

- H.  BACKFRAME**
- Wood clad with:
  - Gray plastic clad with:

- 24 GA white stucco steel
- 24 GA white smooth steel
- 24 GA 304 stucco stainless steel
- OTHER:

- I.  KICKPLATES  Trackside  Wallside**
- Height:  18"  24"  36"  48"  OTHER:
- Aluminum diamond tread (1/8" thick)
  - 18 GA 304 2B stainless steel
  - OTHER:

- J.  LOCKING DEVICE - Hasp Type**
- TRACKSIDE  WALLSIDE
  - with emergency release
  - no emergency release

- K.  ( ) VISION PANEL - 24" x 24"  Insulated  Heated**

