



OPERATING TEMPERATURE		
DOOR	HINGE SIDE	WALL SIDE

APPROVED BY: _____ DATE: _____

Design drawings are for use to verify size, required clearances, and providing confirmation of options requested. Actual production design and components may vary but will not exceed illustrated clearances.

IMPORTANT
Factory may alter door construction and hardware from design illustrated. Factory will not exceed illustrated clearances.

FOR : _____ P.O. # _____ DATE: _____

JOB : _____ F.O. # _____ TAG: _____

Door#	Qty	Width In Clear	Height In Clear	Door Type	Jamb	Hinge Location	Serial Number
				5 1/2" Freezer		Right Hand	

**COLD STORAGE DOOR
OVERLAP DOOR**
SINGLE LEAF 5 1/2" Freezer
MODEL 740 LWT

INSTALLATION REQUIREMENTS

- I. Floor under door must be level and smooth
- II. Wall behind face frame must be smooth in a common plane.
- III. Mounting holes (drilled in field - by others).

DOOR PANEL AND FRAME

- A. Door Panel**
- 24 GA White metal
 - 24 GA 304 stainless steel
 - FRP (White)
 - Other
- Stucco
 Smooth
- B. Face frame** Plastic Wood
- 24 GA White metal
 - 24 GA 304 stainless steel
 - Other
- Stucco
 Smooth
- C. Latch**
- Outside Handle (Plastic)
- D. Interior Release**
- Inside Handle (Plastic)
- E. Hinge**
- Overlap Hinges (Plastic)
- F. Fasteners** Galvanized Stainless Steel

OPTIONS

- G. Freezer Door (GASKET HEAT - FRAME HEAT)**
- 110V electric defrost system at four sides of gasket contact area. Separate 110V connection required in field - by others.
- H. Jamb** Plastic Wood
- 24 GA White metal
 - 24 GA 304 stainless steel
 - Other
- Stucco
 Smooth
- I. Backframe** Plastic Wood
- 24 GA White metal
 - 24 GA 304 Stainless steel
 - Other
- Stucco
 Smooth
- J. Wind Chain**
- Standard Stainless Steel
- K. Hood**
- Matched to hinged panel steel
 - Other
- L. Kickplate**
- Hingeside Wallside
- Height:** 18" 24" 36" 48" Other
- Aluminium diamond tread (1/8" thick)
 - 18 GA 304 #4 stainless steel (smooth)
 - Other